

Model LD - "Loading Devices"

NEW -- Safely Apply Load to Non-Registration Meters

Designed to safely apply load to "non-registration" meters. May also be used for "timed load" field meter testing. Light-weight, compact, polycarbonate construction. The Marwell Load Device is constructed of Poly-Carbonate for durability and safety. Device leads are 42 inches in length and are available with probes or Mueller clips. Protected by an internal thermal overload switch.



MARWELL
SP-LD-277-480-P-MC
Shown on Left



MARWELL
SP-LD-120-240-PBL
Shown on Right

SPECIFICATIONS & ORDERING INFORMATION:

<u>277/480 Volt Box with Handle</u>	<u>120/240 Volt Compact Tube</u>	<u>Description</u>
SP-LD-277-480-PBL	SP-LD-120-240-PBL	Probes on Both Leads
SP-LD-277-480-MCBL	SP-LD-120-240-MCBL	Mueller Clip Both Leads
SP-LD-277-480-P-MC	SP-LD-120-240-P-MC	Probe on one Lead - Mueller Clip on Other

Wattage:

2600 Watts on 480 Volt Meters

900 Watts on 277 Volt Meters

1500 Watts on 240 Volt Meters

350 Watts on 120 Volt Meters

Size:

8.5" H x 4.38" W x 3.5" Deep

3" Diameter x 5.5" H

For information email sales@marwellcorp.com



World's leading manufacturer of UL Listed meter socket adapters

MARWELL CORPORATION



PO BOX 139 * MENTONE, CA 92359 * 909-794-4192 * FAX 909-794-0250